	ELEVATORS & LIFTS KEY FEATURES AND BENEFITS	
	Commercial or Residential lift for applications requiring larger platforms or load	
STANDARD OPTIONS		
• · ·		
≻	Modular steel cab design for robust, long lasting performance	
\succ	Variety of Wall Finishes in either economical baked polyester solid steel or fire rated plastic	
	laminate hang on panels <u>Variety of Doors available</u> automatic two speed sliding or swing type in manual or automatic	
	operation	
\succ	Up to 25 ft of travel allowed on commercial applications, up to 40 ft available for residential	
\succ		
	Over Speed Governor is available as required by codes. Digital Floor Indicators in hall calls and car operating panel confirm the location of the elevator	
	istom sizes, shapes, designs, finishes, heights and configurations all available	
Ride	e Quality	
K	Eleventer Ovide Deil new idea are eth isinte and stable vide	
	Elevator Guide Rail provides smooth joints and stable ride Structural Design of cab and sling eliminates deflection and unwanted cab movement	
	<u>High-Tech Polyurethane Guide Shoes</u> reduce friction and noise normally associated with rollers	
>		
≻	Commercial Buttons and Fixtures that have to meet the more stringent passenger elevator testi	
	and design criteria	
>		
>	Matched, factory assembled and tested <u>Pump/Motor Assemblies</u> Plug-N-Play Wiring ensures correct and stable connections throughout the installation	
afet	y Devices	
\succ	<u></u>	
	loses tension	
	Negative Pressure Module valve prevents car movement if hydraulic pressure is lost	
~	Backup Lighting powered by emergency battery	
≻	Flow Control Valve to prevent over-speed in the down direction	
	Flow Control Valve to prevent over-speed in the down direction	
۶	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator c	
	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator c move Light Curtain standard when 2 speed doors ordered to ensure passenger safety.	
A A Hyd	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator c move Light Curtain standard when 2 speed doors ordered to ensure passenger safety.	
A A Hyd	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator of move Light Curtain standard when 2 speed doors ordered to ensure passenger safety.	
A A Hyd	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator of move Light Curtain standard when 2 speed doors ordered to ensure passenger safety.	
A A Hyd Con	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator c move Light Curtain standard when 2 speed doors ordered to ensure passenger safety.	
A A A Hyd Con	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator c move Light Curtain standard when 2 speed doors ordered to ensure passenger safety. Iraulic Drive System acord introduced the 1:2 Cable Hydraulic Drive System to the residential lift indust <u>1:2 Cable Hydraulic Drive System</u> means 1 foot of cylinder rod movement for 2 feet of cab traver Solid, accurately machined <u>Cylinder Rod</u> provides a stiff column for a high quality ride <u>Twin Lip Cup</u> high performance seal provides for cylinder rod stability - virtually eliminating	
A A Hyd Con	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator c move Light Curtain standard when 2 speed doors ordered to ensure passenger safety. Interlocks Provided the 1:2 Cable Hydraulic Drive System to the residential lift indust 1:2 Cable Hydraulic Drive System means 1 foot of cylinder rod movement for 2 feet of cab traver Solid, accurately machined Cylinder Rod provides a stiff column for a high quality ride Twin Lip Cup high performance seal provides for cylinder rod stability - virtually eliminating leakage	
A A A Hyd Con	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator c move Light Curtain standard when 2 speed doors ordered to ensure passenger safety. Interlocks Provided the 1:2 Cable Hydraulic Drive System to the residential lift indust 1:2 Cable Hydraulic Drive System means 1 foot of cylinder rod movement for 2 feet of cab traver Solid, accurately machined Cylinder Rod provides a stiff column for a high quality ride Twin Lip Cup high performance seal provides for cylinder rod stability - virtually eliminating leakage Variable Speed Proportional Valve provides for the smoothest, most consistent ride in the	
A A Hyd Con A A A A	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator of move Light Curtain standard when 2 speed doors ordered to ensure passenger safety. Introduced the 1:2 Cable Hydraulic Drive System to the residential lift indust 1:2 Cable Hydraulic Drive System means 1 foot of cylinder rod movement for 2 feet of cab traver Solid, accurately machined Cylinder Rod provides a stiff column for a high quality ride Twin Lip Cup high performance seal provides for cylinder rod stability - virtually eliminating leakage Variable Speed Proportional Valve provides for the smoothest, most consistent ride in the industry, regardless of the weight load in the cab	
A A Hyd Con A A A A A	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator c move Light Curtain standard when 2 speed doors ordered to ensure passenger safety. Interlocks Provided the 1:2 Cable Hydraulic Drive System to the residential lift indust accord introduced the 1:2 Cable Hydraulic Drive System to the residential lift indust 1:2 Cable Hydraulic Drive System means 1 foot of cylinder rod movement for 2 feet of cab traver Solid, accurately machined Cylinder Rod provides a stiff column for a high quality ride Twin Lip Cup high performance seal provides for cylinder rod stability - virtually eliminating leakage Variable Speed Proportional Valve provides for the smoothest, most consistent ride in the industry, regardless of the weight load in the cab Spring isolated Submersible Motor and Pump provide for a smooth, quiet operation	
A A Hyd Con A A A A	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator c move Light Curtain standard when 2 speed doors ordered to ensure passenger safety. Interlocks Provided the 1:2 Cable Hydraulic Drive System to the residential lift industry accord introduced the 1:2 Cable Hydraulic Drive System to the residential lift industry 1:2 Cable Hydraulic Drive System means 1 foot of cylinder rod movement for 2 feet of cab traver Solid, accurately machined Cylinder Rod provides a stiff column for a high quality ride Twin Lip Cup high performance seal provides for cylinder rod stability - virtually eliminating leakage Variable Speed Proportional Valve provides for the smoothest, most consistent ride in the industry, regardless of the weight load in the cab Spring isolated Submersible Motor and Pump provide for a smooth, quiet operation Electro-Proportional Valve controls the descent of the elevator further reducing power	
A A Hyd Con A A A A A	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator c move Light Curtain standard when 2 speed doors ordered to ensure passenger safety. Interlocks Provided the 1:2 Cable Hydraulic Drive System to the residential lift industry accord introduced the 1:2 Cable Hydraulic Drive System to the residential lift industry 1:2 Cable Hydraulic Drive System means 1 foot of cylinder rod movement for 2 feet of cab traver Solid, accurately machined Cylinder Rod provides a stiff column for a high quality ride Twin Lip Cup high performance seal provides for cylinder rod stability - virtually eliminating leakage Variable Speed Proportional Valve provides for the smoothest, most consistent ride in the industry, regardless of the weight load in the cab Spring isolated Submersible Motor and Pump provide for a smooth, quiet operation Electro-Proportional Valve controls the descent of the elevator further reducing power requirements and noise	
A A Hyd Con A A A A A	Flow Control Valve to prevent over-speed in the down direction Interlocks Provided, which maintain the door in the closed and locked position before elevator c move Light Curtain standard when 2 speed doors ordered to ensure passenger safety. Interlocks Provided the 1:2 Cable Hydraulic Drive System to the residential lift indust accord introduced the 1:2 Cable Hydraulic Drive System to the residential lift indust 1:2 Cable Hydraulic Drive System means 1 foot of cylinder rod movement for 2 feet of cab traver Solid, accurately machined Cylinder Rod provides a stiff column for a high quality ride Twin Lip Cup high performance seal provides for cylinder rod stability - virtually eliminating leakage Variable Speed Proportional Valve provides for the smoothest, most consistent ride in the industry, regardless of the weight load in the cab Spring isolated Submersible Motor and Pump provide for a smooth, quiet operation Electro-Proportional Valve controls the descent of the elevator further reducing power	